

# PRODUCT SPECIFICATION & TECHNICAL DATASHEET

# FR29 - Bizflame Work FR Hood

**Collection:** Bizflame<sup>™</sup> Work

Range: Flame Resistant Multi-Norm

Shell Fabric: Bizflame Work: 99% Cotton, 1% Carbon

Fibre, 210g

Outer Carton: 50

### **Product information**

This insulating FR liner is suitable to be worn with most helmets. Four Hook & Loop straps attach the liner to helmets for a secure fit. Can be worn with a chin strap.

#### Bizflame™ Work

BizFlame $^{\text{\tiny TM}}$  Work has been developed and designed using the highly innovative Bizflame $^{\text{\tiny TM}}$  Work flame resistant fabric with added anti-static properties. Certified to a range of international standards.

#### Flame Resistant Multi-Norm

This industry leading flame resistant range provides multi-standard protection for hazardous environments. These state of the art products are the result of years of experience combined with advanced technology and market research. Commitment to the health, safety and comfort of the wearer can be seen in the wide range of products suitable for all climates and end uses.

## **Standards**

EN ISO 11612 (A1+A2, B1, C1, E2, F1) EN ISO 11611 Class 1 (A1+A2) EN 1149 -5



## **Features**

- · Hook and loop strap for safe and secure fit
- Back elastic for ease of movement
- Lined for added warmth and comfort
- Compatible with most helmets
- 40+ UPF rated fabric to block 98% of UV rays
- Suitable to be worn in an ATEX environment
- CE certified



## PRODUCT SPECIFICATION & TECHNICAL DATASHEET

FR29 - Bizflame Work FR Hood **Commodity Code: 6506108000** 

**Test House** 

SATRA Technology Europe Ltd (Notified Body No.: NB: 2777)

Bracetown Business Park

D15 YN2P, Ireland

Cert No: 2777/24999-01/E00-00

**Wash Care** 

# **Carton Dimensions/Weight**

| Item    | Colour | Len  | Wid  | Hgt  | Weight(Kg) | Cubic(m³) | EAN13         | GTIN/DUN14     |
|---------|--------|------|------|------|------------|-----------|---------------|----------------|
| FR29NAR | Navy   | 43.0 | 28.0 | 43.0 | 0.1480     | 0.0518    | 5036108348183 | 15036108836809 |